

HARNESS, DICKEY & PIERCE, P.L.C.

Attorneys and Counselors
5445 Corporate Drive, Suite 400
Troy, Michigan 48098-2683
Phone: 248-641-1600
Fax: 248-641-0270
St. Louis, MO • Washington, D.C.

DATE: June 19, 2002

NO. OF PAGES (INCLUDING THIS PAGE): 2

FOR: T. Ton

COMPANY: USPTO

FAX NO.: 703-746-4707

PHONE:

ORIGINAL WILL FOLLOW BY:

- ☐ REGULAR MAIL
☐ OVERNIGHT MAIL
☐ COURIER
☐ WILL NOT FOLLOW

FROM: Timothy D. MacIntyre

9319S-000063

Please let us know by phone or fax if you do not receive any of these pages.

COMMENTS:

Once you have had an opportunity to review the proposed claim, please contact me at 248-641-1230 to further discuss this matter.

***** NOTICE *****

The information contained in this telefax transmission is intended only for the individual to whom or entity to which it is addressed. It may also contain privileged, confidential, attorney work product or trade secret information which is protected by law. If the reader of this message is not the intended recipient, or an employee or agent responsible for delivering the message to the addressee, the reader is hereby notified that any dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please immediately notify us by telephone and return the original message to us at the address above via the U.S. Postal Service. We will reimburse you for any reasonable expense (including postage) for the return of the original message.

PROPOSED CLAIM

Serial No. 09/068,052
Examiner Toan Ton

In Fujikama, Applicant notes that an insulating layer (17) is disposed on the pixel electrode (i.e., the second conductive layer (9)), and thus the pixel electrode does not have a region in which no insulating film is disposed on the pixel electrode.

8. (Thrice Amended) A liquid-crystal display device comprising:
- a first substrate having an inner surface;
 - a second substrate having an inner surface;
 - a liquid-crystal layer disposed between said first and second substrates;
 - a wiring layer formed on at least one of said inner surfaces of said first and second substrates, said wiring layer including a connection portion;
 - an insulating film disposed on at least a portion of the wiring layer, the connection portion being free of the insulating film; and
 - a pixel electrode connected to the connection portion of said wiring layer,
- [; and an insulating film overlapping at least a portion of the wiring layer, such that] the pixel electrode having a region in which no insulating film is disposed on [overlaps] the pixel electrode.